

[PREMIER collection]



	PC0.5	PC1.5	PC33.5	PC3.5	PC9.5	PC-Surround-II	PC60 CA
Description:	2-way bookshelf	2-way bookshelf	3-way LCR	3-way LCR	4-way tower	3-way switchable bipole/dipole surround	2-way bookshelf
Tweeter/ Midrange:	1" soft dome	1" soft dome	1" soft dome	1" soft dome/ 1.5" soft dome	1" soft dome/1.5" soft dome	(2) 1" soft dome/ (2) 4" Poly/NBR	1" soft dome
Woofers:	5.25" RPF™/NBR	6.5" RPF™/NBR	(2) 5.25" RPF™/NBR	(2) 6.5" RPF™/NBR	(3) 6.5" RPF™/NBR	6.5" RPF™/NBR	6.5" RPF™/NBR
Frequency Response:	58-22,000 Hz	40-22,000 Hz	56-22,000 Hz	36-22,000 Hz	32-22,000 Hz	60-22,000 Hz	60-22,000 Hz
Dimensions:	11.5" H x 6.9" W x 9.6" D	13.6" H x 7.9" W x 12.3" D	6.9" H x 18" W x 9.6" D	22" H x 7.9" W x 12.3" D	45.5" H x 9" W x 14.7" D	15.25" H x 14.5" W x 5.25" D	13.25" H x 8.625" W x 8.25" D
Colors:	Gloss Black	Gloss Black	Gloss Black	Gloss Black	Gloss Black	Gloss Black or Satin White	Black Oak or Oak

[PHASE velocity]



	V52	V62	V626	V5520	V-Surround-II	CineMicro System	Center	Satellite
Description:	2-way bookshelf	2-way bookshelf	3-way tower	2-way LCR	2-way switchable bipole/dipole surround speaker	5.1 home theater system	2-way LCR	2-way bookshelf
Tweeter/ Midrange:	1" soft dome	1" soft dome	1" soft dome	1" soft dome	(2) 1" soft dome	.75" soft dome	.75" soft dome	.75" soft dome
Woofers:	5.25" VDT™/NBR	6.5" VDT™/NBR	(2) 6.5" VDT™/NBR	5.25" VDT™/NBR	5.25" VDT™/NBR	3" Poly/NBR & 8" polypropylene	(2) 3" Poly/NBR	3" Poly/NBR
Bass Radiator:	N/A	N/A	N/A	5.25" VDT™/NBR	N/A	N/A	N/A	N/A
Frequency Response:	58-20,000 Hz	45-20,000 Hz	32-20,000 Hz	58-20,000 Hz	70-20,000 Hz	36-20,000 Hz	110-20,000 Hz	110-20,000 Hz
Dimensions:	10.75" H x 7.4" W x 8.53" D	13.25" H x 8.25" W x 9.53" D	40.5" H x 8.25" W x 9.53" D	17.25" H x 8.53" D	9" H x 11.94" W x 4.5" D	36-20,000 Hz	4.5" H x 10.25" W x 4.75" D	6.75" H x 4.25" W x 4.75" D
Colors:	Black Ash	Black Ash	Black Ash	Black Ash	Black Ash or Satin White	Gloss Black, Black Ash Sub	Gloss Black	Gloss Black

[CINEmicro®]

[HV subwoofers]



	HV81	HV101	HV121	POWER-FL8	POWER-FL10	POWER-FL12
Description:	8" High velocity subwoofer	10" High velocity subwoofer	12" High velocity subwoofer	8" High performance subwoofer	10" High performance subwoofer	12" High performance subwoofer
Woofers:	8" Poly/NBR	10" Poly/NBR	12" Poly/NBR	8" Poly/NBR	10" Poly/NBR	12" Poly/NBR
Passive Radiator:	N/A	N/A	N/A	8" Poly/NBR	10" Poly/NBR	12" Poly/NBR
Amplifier Power:	100 W continuous, 200 W peak	100 W continuous, 200 W peak	100 W continuous, 200 W peak	250 W continuous, 600 W peak	250 W continuous, 600 W peak	250 W continuous, 600 W peak
Frequency Response:	36-200 Hz	29-200 Hz	25-200 Hz	32-150 Hz	26-150 Hz	25-150 Hz
Dimensions:	14.125" H x 10.75" W x 15.75" D	16.125" H x 13.75" W x 16.75" D	17.25" H x 15.75" W x 18.25" D	14.625" H x 11.125" W x 15.25" D	16.25" H x 12.5" W x 18.5" D	18" H x 15" W x 20.75" D
Colors:	Black Ash	Black Ash	Black Ash	Black Ash	Black Ash	Black Ash

[POWER-fl subwoofers]

[PC-sub w/ subwoofers]



	PC SUB WL-10	PC SUB WL-12
Woofers:	10" Poly/NBR	12" Poly/NBR
Passive Radiator:	10" Poly/NBR	12" Poly/NBR
Amplifier Power:	300 W continuous, 900 W peak	300 W continuous, 900 W peak
Wireless:	2.4 GHz uncompressed audio streaming: lossless	2.4 GHz uncompressed audio streaming: lossless
Frequency Response:	24-120 Hz	22-120 Hz
Dimensions:	13" H x 13.375" W x 14.5" D	15.5" H x 16.25" W x 16.325" D
Colors:	Gloss Black	Gloss Black

[TEATRO® soundbars]



	TEATRO PC3.0	TEATRO V3.0	TSB3.0
Description:	3-way LCR soundbar	2-way LCR soundbar	Ultra-thin LCR soundbar
Tweeter/ Midrange:	(3) 1" soft dome/ 1.5" dome	(3) 1" soft dome	(3) .75" soft dome
Woofers:	(3) 5.25" RPF™/NBR	(3) 5.25" VDT™/NBR	(3) 3" Poly/NBR
Additional Drivers:	Spatial Field Expanders™, (2) 1.5"	Spatial Field Expanders™, (2) 1"	Spatial Field Expanders™, (2) 1"
Frequency Response:	52-22,000 Hz	55-22,000 Hz	75-20,000 Hz
Dimensions:	7" H x 40" W x 4.5" D	7" H x 40" W x 4.5" D	6.75" H x 43" W x 1.5" D (where it meets tv)
Colors:	Satin Black or Gloss Black	Gloss Black	Brushed Black

[TEATRO® ultra-thin series]



	TFS1.0	TCE1.5
Description:	Front & surround channel	CLR channel
Tweeter:	.75" soft dome	(2) .75" soft dome (1 LR/1 Center)
Woofers:	(2) 3" Poly/NBR	(3) 3" Poly/NBR (2 LR/1 Center)
Bass Radiator:	(2) 3" Poly/NBR	(2) 3" Poly/NBR (LR)
Frequency Response:	65-20,000 Hz	65-20,000 Hz
Dimensions:	4.35" Diameter	6.75" H x 4.3" W x 1.5" D
Colors:	Gloss Black	Brushed Black

[SPACIA® series]



	HS15	CI-MM3-II	CI1.5	CI15
Description:	3" full-range pendant mount	In-wall full-range	In-ceiling with integrated metal backcan/ bypassable 25/70.7/100 V transformer	In-wall full-range
Woofers:	3" Poly/NBR	3" Poly/NBR	3" Poly/NBR	3" Poly/NBR
Frequency Response:	120-22,000 Hz	80-22,000 Hz	135-22,000 Hz	135-22,000 Hz (+/- 5 dB)
Dimensions:	3.35" H x 4.35" D	4.1" H x 4.1" W x 1.9" D	6.3" Diameter x 4.25" Deep	5" H x 5" W x 4.125" D
Cutout Dimensions:	N/A	Will fit in pre & post installation J boxes	5.5"	4.35" H x 4.35" W
Mounting Depth:	N/A	14.17" Diameter x 15.1" H	3.5"	3.5"
Colors:	White (paintable)	White Paintable Grille	White Paintable Grille	White Paintable Grille

[SOLARIS® outdoor series]



	SPF-15	SPF-25	SPF-35	SPF-55	SPF-85	IW200
Description:	full-range surface-mount	2-way surface-mount	2-way surface-mount	2-way coaxial outdoor	2-way coaxial outdoor	In-wall subwoofer with sealed enclosure
Tweeter:	N/A	1" titanium dome	1" titanium dome	1" aluminum dome	1" aluminum dome	(2) 8" Poly/NBR
Woofers:	3" Poly/NBR	5.25" Poly/NBR	6.5" Poly/NBR	5.25" Poly/NBR	8" Poly/NBR	350 W peak
Frequency Response:	120-22,000 Hz	64-20,000 Hz	48-20,000 Hz	62-22,000 Hz	38-22,000 Hz	25-160 Hz
Dimensions:	4.35" Diameter	11" H x 6.75" W x 6.25" D	12" H x 8.75" W x 7.75" D	14.1" Diameter x 15.1" H	14.17" Diameter x 16.42" H	Enclosure mounts between 16" on-center 2" x 4" stud wall
Mounting Depth:	3.81" including bracket	N/A	N/A	N/A	N/A	Requires P350 subwoofer amp
Colors:	Black or White	Black or White	Black or White	Sandstone or Green	Sandstone or Green	White Paintable Grille

[SUBwoofer]



[CS professional micro series]



	CS-6R/Micro	CS-6DVT/Micro	CS-8R/Micro
Description:	2-way	2-way dual voice coil	2-way
Tweeter:	.75" pivoting soft dome	(2) .75" soft dome	.75" pivoting soft dome
Woofers:	6.5" coaxial Poly/NBR	6.5" coaxial Poly/NBR	8" coaxial Poly/NBR
Frequency Response:	55-20,000 Hz	55-20,000 Hz	48-20,000 Hz
Diameter:	9.5"	9.5"	10.75"
Depth:	3.4"	3.625"	3.875"
Cutout Diameter:	8.125"	8.125"	9.5"
Mounting Depth:	2.875"	3"	3.375"
Colors:	White Paintable Grille	White Paintable Grille	White Paintable Grille

[CI custom install series]



	CI6.0 IX QM	CI6.1X	CI6.2 X	CI7.3 X
Description:	2-way in-ceiling	2-way in-ceiling	2-way switchable mono/stereo/bipole/dipole in-ceiling speaker & surround	3-way in-ceiling
Tweeter:	1" pivoting soft dome	1" variable axis soft dome	(2) .75" synthetic soft dome	1" variable soft dome
Midrange:	N/A	N/A	N/A	1.5" soft dome
Woofers:	6.5" Poly/NBR	6.5" Glass Fiber/NBR	6.5" Glass Fiber/NBR	8" Glass Fiber/NBR
Frequency Response:	55-20,000 Hz	40-22,000 Hz	45-20,000 Hz	38-22,000 Hz
Diameter:	9.63"	9.34"	9.34"	11"
Depth:	4.6"	4.625"	4.625"	5.25"
Cutout Diameter:	8.375"	7.875"	7.875"	9.625"
Mounting Depth:	4"	4.375"	4.375"	5"
Weight:	2.75 lbs.	4.5 lbs.	4.5 lbs.	6 lbs.
Colors:	White Paintable Grille	White Paintable Grille	White Paintable Grille	White Paintable Grille

[CI custom install series]



	CI20 X	CI60 VII	CI70 X	CI-SURR X	CI110 II	CI150
Description:	2-way in-wall	2-way in-wall	3-way in-wall	2-way switchable mono/stereo/bipole/dipole in-wall surround speaker	2.5-way in-wall	2-way in-wall produces 3 front channels from 2 speakers
Tweeter:	1" variable axis soft dome	1" pivoting soft dome	1" variable axis soft dome	(2) 1" synthetic soft dome	1" pivoting soft dome	1" pivoting soft dome (2 LR/1 Center)
Woofers:	6.5" Glass Fiber/NBR	6.5" Glass Fiber/NBR	7" Glass Fiber/NBR	6.5" Glass Fiber/NBR	(2) 6.5" RPF™/NBR	(3) 5.25" RPF™/NBR (2 LR/1 Center)
Frequency Response:	48-20,000 Hz	40-22,000 Hz	35-22,000 Hz	45-20,000 Hz	32-22,000 Hz	70-22,000 Hz
Dimensions:	11.375" H x 8.63" W x 3.75" D	11.81" H x 8.63" W x 3.9" D	12.57" H x 8.63" W x 3.75" D	12.57" H x 8.63" W x 3.75" D	21.5" H x 10" W x 4.25" D	31.375" H x 8.125" W x 4.25" D
Cutout Dimensions:	11.375" H x 7.375" W	10.75" H x 7.5" W	11.375" H x 7.375" W	11.375" H x 7.375" W	20.375" H x 8.875" W	30.375" H x 7" W
Mounting Depth:	3.5"	3.5"	3.5"	3.5"	4"	3.875"
Weight:	5 lbs.	4.75 lbs.	5.5 lbs.	5 lbs.	21 lbs.	18.5 lbs.
Colors:	White Paintable Grille	White Paintable Grille	White Paintable Grille	White Paintable Grille	White Paintable Grille	White Paintable Grille

[AMPlifier]



	P350
Description:	P350 Class-G high current subwoofer/full-range mono block amplifier
Amplifier Power:	350 W RMS @ 4Ω, 700 W peak, 225 W RMS @ 8Ω, 400 W peak
Crossover Frequency:	Low Pass 40-120 Hz adjustable @ 24 dB/octave
LFE Frequency Response:	20-500 Hz
Full-Range Response:	10-20,000 Hz +/- 0/-25 dB, 5-6,000 Hz +/- 0/-3 dB
Low Frequency EQ:	-3 dB to +6 dB @ 30 Hz
Max Current Consumption:	3A @ 8Ω, 5.5A @ 4Ω continuous
Dimensions:	2" H x 17.25" W x 13.25"