

The drivers and crossover network, mounted on their baffle, are completely interchangeable, so your CI Series speakers can easily be upgraded to a higher performance model in the future.

High-quality binding posts are used to secure speaker cables upon installation.

The speaker grille as well as the frame can be painted or covered with wallpaper to match your home's decor.

During construction of your home, only the frames of your CI Series speakers are installed. This way, the chance of damage to the speakers themselves is eliminated. Wiring is routed into place and secured until construction is completed, when the speakers' driver/crossover assemblies are mounted in the frame.

S P E C I F I C A T I O N S



CI-10 IV

FREQUENCY RANGE
55 Hz - 20kHz

RECOMMENDED AMPLIFIER POWER
10 - 50 WATTS

IMPEDANCE
8 Ohms

SPEAKER PROTECTION
Protection Circuit

WOOFER/MIDRANGE
5.1/4" Polypropylene Cone

TWEETER
3/4" Dome

OUTSIDE DIMENSION WITH FLANGE
11 13/16" h x 8 5/8" w

MOUNTING DEPTH REQ'D
3 1/8"

REQUIRED CUTOUT DIMENSION
10 3/4" h x 7 1/2" w

CI-20 IV

FREQUENCY RANGE
50 Hz - 20kHz

RECOMMENDED AMPLIFIER POWER
10 - 60 WATTS

IMPEDANCE
8 Ohms

SPEAKER PROTECTION
Protection Circuit

WOOFER/MIDRANGE
6.1/2" Polypropylene Cone

TWEETER
3/4" Dome

OUTSIDE DIMENSION WITH FLANGE
11 13/16" h x 8 5/8" w

MOUNTING DEPTH REQ'D
3 1/4"

REQUIRED CUTOUT DIMENSION
10 3/4" h x 7 1/2" w

CI-40 IV

FREQUENCY RANGE
45 Hz - 20kHz

RECOMMENDED AMPLIFIER POWER
10 - 70 WATTS

IMPEDANCE
8 Ohms

SPEAKER PROTECTION
Protection Circuit

WOOFER/MIDRANGE
6.1/2" Polypropylene Cone

TWEETER
1" Soft Dome

OUTSIDE DIMENSION WITH FLANGE
11 13/16" h x 8 5/8" w

MOUNTING DEPTH REQ'D
3 3/8"

REQUIRED CUTOUT DIMENSION
10 3/4" h x 7 1/2" w

CI-60 IV

FREQUENCY RANGE
40 Hz - 20kHz

RECOMMENDED AMPLIFIER POWER
10 - 80 WATTS

IMPEDANCE
8 Ohms

SPEAKER PROTECTION
Protection Circuit

WOOFER/MIDRANGE
6.1/2" RPF Solid Piston

TWEETER
1" Soft Dome

OUTSIDE DIMENSION WITH FLANGE
11 13/16" h x 8 5/8" w

MOUNTING DEPTH REQ'D
3 1/2"

REQUIRED CUTOUT DIMENSION
10 3/4" h x 7 1/2" w

CI-SUB IV

FREQUENCY RANGE
28 Hz - 90Hz

RECOMMENDED AMPLIFIER POWER
25 - 100 WATTS/channel

IMPEDANCE
8 Ohms Dual Voice Coil

WOOFER
6 x 9" Cone

OUTSIDE DIMENSION WITH FLANGE
11 13/16" h x 8 5/8" w

MOUNTING DEPTH REQ'D
3 5/8"

REQUIRED CUTOUT DIMENSION
10 3/4" h x 7 1/2" w

INSTALLATION NOTE: Although the CI Series can be installed by anyone, we recommend professional assistance because of the complexities of wiring and of determining the proper placement for optimum performance.

Your Phase Technology Retailer is: