

Introduces the **NEW PC 6.5** A Zero-diffraction Speaker System



Specifications

DRIVERS

Low frequency	8" RPF™ solid-piston driver
Midrange	5 1/4" RPF™ solid-piston driver
High frequency	1" soft dome

CROSSOVER FREQ. 450 Hz, 2.0 kHz

FREQUENCY RANGE 42-20,000 Hz ± 2 dB

SENSITIVITY 88 dB / 2.83 V / 1 M

RECOMMENDED

AMP POWER 25 - 100 watts

IMPEDANCE 4 ohms

DIMENSIONS 36 3/8" H x 11" W x 9" D

SHIPPING WEIGHT 58 lbs. each

The zero-diffraction **PC 6.5** is a three-way system employing the company's proprietary Unicell™ acoustic treatment surrounding the patented soft-dome tweeter. This unique technology virtually eliminates cabinet and grille diffraction effects and produces an undistorted wave front. As a result, music is presented with image clarity and flat frequency response approximating that of a true point source. The speakers are designed for best performance *with the removable grilles in place.*

The patented RPF™ solid-piston midrange and bass drivers combine with the tweeter to launch a wave front that further enhances imaging, detail and frequency balance over a wide listening area. Cabinet construction is of exceptionally rigid one-inch-thick, real wood veneer board. The speaker also uses computer-grade polypropylene capacitors and five-way, 24kt goldplated binding posts.

The new **PC 6.5** represents a major innovation and advancement in loudspeaker design. Audition these superb new speakers now at your Phase Technology dealer.