

# CS PROFESSIONAL

CS-6R • CS-6R DVT • CS-8R

The CS professional series from Phase Technology redefines what you should expect in an affordable in-ceiling speaker, offering the looks, the performance and the cost of most other manufacturers' premium-priced in-ceiling solutions.

The CS-6R, CS-6R DVT and CS-8R, incorporate features most manufacturers commonly offer in their top of the line in-ceiling speakers, such as polypropylene cones with butyl rubber surrounds, swiveling dome tweeters, a true high-pass/low-pass crossover, high-quality metal binding posts and micro-flange, magnetic grilles. The speakers' micro-flange grilles are some of the thinnest on the market,

with a bezel that is nearly invisible. Grilles are also paintable to blend in with the ceiling.

Engineered to handle the dynamic range of both traditional stereo and modern multi-channel audio sources, each CS model delivers precise tonal balance with a crisp, clear articulation of each frequency. For rooms requiring an off-axis mounting situation (such as a sloped ceiling), the CS Professional Series offers pivoting tweeters, allowing the speakers to be properly aimed at the listening area.



## CS-6R

**Description:** 6.5" Coax In-Ceiling  
**Tweeter:** .75" Variable Axis Soft Dome  
**Woofer:** 6.5" Coaxial Polypropylene with NBR Surround  
**Frequency Response:** 55 Hz - 20 kHz  
**Sensitivity:** 87 dB  
**Impedance:** 8Ω  
**Power Handling:** 5-100 Watts  
**Dimensions:** 9.1" Diameter x 3.4" Depth  
**Cutout Diameter:** 8.062"  
**Weight:** 2 lbs.  
**Grille:** White Powder-Coated Magnetic Micro-Flange (paintable)



## CS-8R

**Description:** 8" Coax In-Ceiling  
**Tweeter:** .75" Variable Axis Soft Dome  
**Woofer:** 8" Coaxial Polypropylene with NBR Surround  
**Frequency Response:** 48 Hz - 20 kHz  
**Sensitivity:** 87 dB  
**Impedance:** 8Ω  
**Power Handling:** 5-120 Watts  
**Dimensions:** 10.625" Diameter x 3.875" Depth  
**Cutout Diameter:** 9.625"  
**Weight:** 4.75 lbs.  
**Grille:** White Powder-Coated Magnetic Micro-Flange (paintable)



## CS-6R DVT

**Description:** 6.5" 2-Way Dual Voice Coil In-Ceiling  
**Tweeter:** (2) .75" Variable Axis Soft Dome  
**Woofer:** 6.5" Polypropylene with NBR Surround  
**Frequency Response:** 55 Hz - 20 kHz  
**Sensitivity:** 87 dB  
**Impedance:** 8Ω  
**Power Handling:** 5-100 Watts  
**Dimensions:** 9.1" Diameter x 3.4" Depth  
**Cutout Diameter:** 8.062"  
**Weight:** 2.5 lbs.  
**Grille:** White Powder-Coated Magnetic Micro-Flange (paintable)