

HS PENDANTS

HS15 • HS24 • HS26 • HS28 • HS28-T



Phase Technology's HS (Hanging Speakers) are ideal for open-ceiling applications such as kitchens, bars, workout rooms and patio areas.

Every aspect of Phase Technology Hanging Series speakers maximizes performance – from the ultra-rigid injection-molded ABS enclosure design to the advanced circuitry that provides true musical reproduction and crystal-clear intelligibility. If you're looking for high-fidelity sound for open or high-ceiling areas, look no further than the HS Series.

HS PENDANTS

HS15 • HS24 • HS26 • HS28 • HS28-LT

HS15



Description: 3" Full-Range Pendant
Woofer: 3" Polypropylene w/ NBR Surround
Frequency Response: 120 Hz - 22 kHz
Sensitivity: 88 dB
Impedance: 8Ω
Power Handling: 10-40 Watts
Dimensions: 3.35" Height, 4.35" Diameter
Height w/ Stabilizing Arm: 5.5"
Weight: 1.4 lbs.
Grille: Corrosion-resistant, Powder-Coated Aluminum
Color Options: White

HS24



Description: 4" Coax, Open-Ceiling Ported Pendant
Tweeter: .75" Silk Dome w/ BroadBeam Ring™
Woofer: 4" Polypropylene w/ NBR Surround
Frequency Response: 140 Hz - 22 kHz
Sensitivity: 85 dB
Impedance: 16Ω
Transformer Size for 25/70.7/100V: 20 W
Power Handling: 10-40 Watts
Dimensions: 7.46" Height, 7.86" Diameter
Weight: 3.9 lbs.
Grille: Powder-Coated Aluminum
Color Options: Black or White

HS26



Description: 6.5" Coax, Open-Ceiling Ported Pendant
Tweeter: 1" Silk Dome w/ BroadBeam Ring™
Woofer: 6.5" Polypropylene w/ NBR Surround
Frequency Response: 100 Hz - 22 kHz
Sensitivity: 87 dB
Impedance: 16Ω
Transformer Size for 25/70.7/100V: 32 W
Power Handling: 10-64 Watts
Dimensions: 10.08" Height, 10.4" Diameter
Weight: 7 lbs.
Grille: Powder-Coated Aluminum
Color Options: Black or White

HS28



Description: 8" Coax, Open-Ceiling Ported Pendant
Tweeter: 1" Silk Dome w/ BroadBeam Ring™
Woofer: 8" Polypropylene w/ NBR Surround
Frequency Response: 100 Hz - 22 kHz
Sensitivity: 92 dB
Impedance: 16Ω
Transformer Size for 25/70.7/100V: 64 W
Power Handling: 10-128 Watts
Dimensions: 12.8" Height, 12.9" Diameter
Weight: 11 lbs.
Grille: Powder-Coated Aluminum
Color Options: Black or White

HS28-LT



Description: 8" Coax, Open-Ceiling Ported Pendant
Tweeter: 1.4" Compression Horn Driver
Woofer: 8" Treated Paper w/ Treated Cloth Surround
Frequency Response: 100 Hz - 22 kHz
Sensitivity: 93 dB
Impedance: 16Ω
Transformer Size for 25/70.7/100V: 64 W
Power Handling: 10-128 Watts
Dimensions: 12.8" Height, 12.9" Diameter
Weight: 14 lbs.
Grille: Powder-Coated Aluminum
Color Options: Black or White