

POWER FL SUBWOOFERS

POWER-FL8 • POWER-FL10 • POWER-FL12



Power FL subwoofers deliver uncompromised bass output. To maximize output and increase excursion, a proprietary butyl rubber surround is virtually double the size of conventional surrounds. The combination of an oversized surround with an ultra long-throw, mineral filled polypropylene woofer, and a downward-firing bass radiator delivers serious bass response and output.

To minimize distortion, this monstrous woofer/surround configuration is attached to a 3/4" to 1" MDF baffle and mated to curved architectural cabinets. A 250 watt servo-controlled amplifier monitors and adjusts output for dynamic, undistorted response. Power FL Series subwoofers also include gain control, a phase switch, variable crossover frequencies, line level inputs, a separate LFE input, and speaker level input.



POWER-FL8

Description: 8" Subwoofer w/ Passive Radiator
Driver: 8" Ultra-Long Throw Mica Graphite Poly Cone w/ NBR Surround
Amplifier Power: 250 W Continuous, 600 W Peak
Frequency Response: 32 Hz - 150 Hz
Speaker Level Inputs: 2x Binding Post Pairs
Line Level Inputs: 2x Stereo & LFE Gold-Plated RCA
Dimensions: 14.625" H x 11.125" W x 15.25" D
Weight: 23 lbs.



POWER-FL10

Description: 10" Subwoofer w/ Passive Radiator
Driver: 10" Ultra-Long Throw Mica Graphite Poly Cone w/ NBR Surround
Amplifier Power: 250 W Continuous, 600 W Peak
Frequency Response: 26 Hz - 150 Hz
Speaker Level Inputs: 2x Binding Post Pairs
Line Level Inputs: 2x Stereo & LFE Gold-Plated RCA
Dimensions: 16.25" H x 12.5" W x 18.5" D
Weight: 30 lbs.



POWER-FL12

Description: 12" Subwoofer w/ Passive Radiator
Driver: 12" Ultra-Long Throw Mica Graphite Poly Cone w/ NBR Surround
Amplifier Power: 250 W Continuous, 600 W Peak
Frequency Response: 25 Hz - 150 Hz
Speaker Level Inputs: 2x Binding Post Pairs
Line Level Inputs: 2x Stereo & LFE Gold-Plated RCA
Dimensions: 18" H x 15" W x 20.75" D
Weight: 42 lbs.