

# SOLARIS® OUTDOOR

SPF-15 • SPF-15-T • SPF-25 • SPF-35 • SPF-55 • SPF-85



PhaseTech's Solaris series of outdoor speakers meets the challenge of delivering high-quality music to any outdoor space. Fully weatherproof and backed by a ten-year warranty, the Solaris line provides outdoor audio performance that is second to none.

Base response is a component often overlooked in outdoor audio, but it is remarkably important considering how difficult it is to provide good bass reinforcement in large, open-air environments. To solve this tricky problem, PhaseTech tunes up the low-end response in the SPF-25 and SPF-35 to properly accentuate this sound characteristic. The bass in these speakers provide would-be overkill for an interior space, but for the challenging acoustics of an outdoor space, the amount is just right.

The Solaris series is comprised of weatherized components for lasting performance outdoors. Each speaker incorporates water-tight fittings, mineral-filled polypropylene cones with butyl surrounds, and powder-coated metal grilles. All hardware also utilizes weather-resistant brass and stainless steel materials. When all of these elements are combined into one finely engineered speaker package, the net result is a series of products that will provide top-of-the-line audio and stand up to the elements for years to come.

Visit [www.phasetech.com](http://www.phasetech.com) to learn more about the Solaris series.

# SOLARIS<sup>®</sup> OUTDOOR

SPF-15 • SPF-15-T • SPF-25 • SPF-35 • SPF-55 • SPF-85

## SPF-15



Description: 3" Full-Range Surface-Mount  
Woofer: 3" Polypropylene w/ NBR Surround  
Frequency Response: 170 Hz - 14 Hz  
Sensitivity: 85 dB  
Impedance: 8Ω  
Recommended Power: 5 - 60 Watts  
Dimensions: 4.35" H x 4.35" W  
Depth Including Mounting Bracket: 3.81"  
Weight: 1.4 lbs.  
Grille: Powder-Coated Aluminum  
Color Options: Black or White

## SPF-35



Description: 6.5" 2-Way Surface-Mount  
Tweeter: 1" Titanium Dome  
Woofer: 6.5" Mineral-Filled Polypropylene w/  
NBR Surround  
Frequency Response: 64 Hz - 20 Hz  
Sensitivity: 88 dB  
Impedance: 8Ω  
Recommended Power: 10 - 120 Watts  
Dimensions: 12" H x 8.75" W x 7.75" D  
Weight: 6.8 lbs.  
Grille: Powder-Coated Aluminum  
Color Options: Black or White

## SPF-15-T



Description: 3" Full-Range Surface-Mount  
Woofer: 3" Polypropylene w/ NBR Surround  
Frequency Response: 170 Hz - 14 Hz  
Sensitivity: 85 dB  
Impedance: 8Ω  
Recommended Power: 5 - 60 Watts  
Transformer: 10 W for 25/70.7/100 V Applications  
Transformer Settings: 10 W, 5 W, 2.5 W, 1.3 W, 0.7 W  
Dimensions: 4.35" H x 4.35" W  
Depth Including Mounting Bracket: 3.81"  
Weight: 1.4 lbs.  
Grille: Powder-Coated Aluminum  
Color Options: Black or White

## SPF-55



Description: 5.25" Coax Omnidirectional  
Tweeter: 1" Aluminum Dome  
Woofer: 5.25" Polypropylene w/ NBR Surround  
Frequency Response: 62 Hz - 22 Hz  
Sensitivity: 85 dB  
Impedance: 4Ω  
Recommended Power: 15 - 60 Watts  
Dimensions: 15.1" Height, 14.1" Diameter  
Weight: 13 lbs.  
Color Options: Green or Sandstone

## SPF-25



Description: 5.25" 2-Way Surface-Mount  
Tweeter: 1" Titanium Dome  
Woofer: 5.25" Mineral-Filled Polypropylene w/  
NBR Surround  
Frequency Response: 64 Hz - 20 Hz  
Sensitivity: 89 dB  
Impedance: 8Ω  
Recommended Power: 10 - 100 Watts  
Dimensions: 11" H x 6.75" W x 6.25" D  
Weight: 5.3 lbs.  
Grille: Powder-Coated Aluminum  
Color Options: Black or White

## SPF-85



Description: 8" Coax Omnidirectional  
Tweeter: 1" Aluminum Dome  
Woofer: 8" Polypropylene w/ NBR Surround  
Frequency Response: 38 Hz - 22 Hz  
Sensitivity: 90 dB  
Impedance: 4Ω  
Recommended Power: 15 - 100 Watts  
Dimensions: 16.42" Height, 14.7" Diameter  
Weight: 16.7 lbs.  
Color Options: Green or Sandstone